



**TYPICAL SECTION**

ALL MEASUREMENTS IN MILLIMETRES

**NOTES:**

1. REFER TO SD 100 OR SD 105 FOR KERB DETAILS.
2. FOR WIDTH MINIMUM OF 100 TO 350mm USE CONTROLLED LOW STRENGTH MATERIAL (CLSM) INFILL.
3. PM 2 / 20 RG TO BE USED INSTEAD OF PM 2 / 20 QG ONLY WHEN SPECIFICALLY APPROVED BY COUNCIL.
4. REFER PAVEMENT DESIGN FOR PAVEMENT THICKNESS

						INFRASTRUCTURE GUIDELINES (SA)			
						SHEET TITLE			
						<b>KERB &amp; WATERTABLE INSTALLATION</b>			
						<b>ABUTTING EXISTING PAVEMENT</b>			
						SCALE			
						1:10 @ A3			
						DRAWING No.		REV	
						<b>SD 110</b>		<b>D</b>	
REV	DESCRIPTION	DATE	DES	DRW	APP				
D	MINOR AMENDMENTS	06.11.2018	AF	AF	MDH				
C	MINOR AMENDMENTS	18.07.2017	JZ	JC	DSL				
B	ISSUED FOR REVIEW	10.05.2016	JZ	DL	DSL				
A	ISSUED FOR REVIEW	15.03.2016	JZ	DL	DSL				
THIS PROJECT HAS BEEN ASSISTED BY THE LOCAL GOVERNMENT RESEARCH AND DEVELOPMENT SCHEME AND INSTITUTE OF PUBLIC WORKS ENGINEERING AUSTRALASIA									