



TYPICAL SECTION

ALL MEASUREMENTS IN MILLIMETRES

NOTES:

1. THE DRAINS SHALL BE LAID ON A GRADE PARALLEL TO THE FINISHED SURFACE.
2. FOR FLUSHOUT RISER DETAILS REFER TO STANDARD DRAWINGS SD 395.
3. WHERE THE SUBGRADE IS CLASSIFIED AS BEING EXPANSIVE, SUBSURFACE PAVEMENT DRAINS SHALL BE DESIGNED TO BE CONTAINED WHOLLY WITHIN THE CAPPING LAYER. IN ADDITION, NO PART OF THE SUBSURFACE DRAINAGE TRENCH SHALL BE LOCATED WITHIN 150mm OF THE UNDERLYING SUBGRADE. IF NECESSARY, THE CAPPING LAYER MAY HAVE TO BE THICKENED TO SATISFY THIS REQUIREMENT.

						INFRASTRUCTURE GUIDELINES (SA)			
						SHEET TITLE			
						TYPICAL PAVEMENT			
						SUBSOIL DRAINAGE			
						SCALE			
						1:10 @ A3			
						DRAWING No.		REV	
						SD 265		C	
REV	DESCRIPTION	DATE	DES	DRW	APP				
C	MINOR AMENDMENTS	06.11.2018	AF	AF	MDH				
B	ISSUED FOR REVIEW	10.05.2016	JZ	DL	DSL				
A	ISSUED FOR REVIEW	15.03.2016	JZ	DL	DSL				
THIS PROJECT HAS BEEN ASSISTED BY THE LOCAL GOVERNMENT RESEARCH AND DEVELOPMENT SCHEME AND INSTITUTE OF PUBLIC WORKS ENGINEERING AUSTRALASIA									