



NOTES:

1. COMPACTION PRESSURE BEHIND ENDWALLS IS NOT TO EXCEED 12.5kPa. REFER (1.5 TONNE VIBRATORY ROLLER).
2. A MAXIMUM PIPE SIZE OF 300Ø FOR THIS ENDWALL ARRANGEMENT.
3. NOT TO BE USED WHERE GENERAL VEHICULAR TRAFFIC IS PRESENT (MAINTENANCE OR EMERGENCY VEHICLES EXCEPTED).
4. ALTERNATIVELY PRECAST ENDWALL MAY BE USED WHERE APPROVED BY COUNCIL.
5. CONCRETE STRENGTH F'C = 25 MPa (MIN.) AT 28 DAYS.
6. MAXIMUM BATTER SLOPE 1V : 2H

ALL MEASUREMENTS IN MILLIMETRES

REV	DESCRIPTION	DATE	DES	DRW	APP
C	ISSUED FOR REVIEW	10.06.2016	JZ	DL	DSL
B	ISSUED FOR REVIEW	10.05.2016	JZ	DL	DSL
A	ISSUED FOR REVIEW	15.03.2016	JZ	DL	DSL

THIS PROJECT HAS BEEN ASSISTED BY THE LOCAL GOVERNMENT RESEARCH AND DEVELOPMENT SCHEME AND INSTITUTE OF PUBLIC WORKS ENGINEERING AUSTRALASIA

INFRASTRUCTURE GUIDELINES (SA)		SCALE NTS @ A3	
SHEET TITLE CONCRETE ENDWALL FOR PIPES UP TO 300mmØ (WALKWAYS, PATHS AND TRACKS)		DRAWING No. SD 365	
		REV C	